



AVEX CCTV's IP68 rated AH35 Weatherproof Camera Housing provides safe and reliable protection for a wide range of cameras in harsh weather conditions.

WHEN SAFETY AND PERFORMANCE MATTERS

The AH35 camera housing is constructed from 316L stainless steel for maximum corrosion protection. The window of the housing is made of 8mm thick tempered glass for extra durability while preserving image quality. Sunshield, Wall mount bracket, Auto-heater and Window Defroster are optional.

The optional wall mount bracket is supplied with swivel joint for easy and accurate positioning of the housing.

The AH35 camera housing can be fitted with a wide range of Analog and Network box cameras and lens or motorized zoom cameras, making it the perfect choice for almost any application.

Cameras are not included. If required, please contact us.

FEATURES

- Stainless Steel 316L
- Suitable for box cameras and lens or motorized zoom cameras
- Temperature Rating: -40°C ~ +60°C (with heater)
- Weather Resistant to IP68 & NEMA 6 & 6P Standards
- Designed for ease of installation and minimal maintenance
- Optional Sunshield, Auto-Heater, Window Defroster & Wall mount bracket
- Fixed mount – Bracket with swivel joint or Base installation

APPLICATIONS

- Offshore Industries
- Marine Industries
- Oil & Gas Industries
- Industrial Environments
- Manufacturing Industries
- Construction Industries

TECHNICAL DATA

COMPLIANCE

IP 68 / Nema Type 6/6P (Factory rated)

MECHANICAL

Construction	316L Stainless Steel
Finishing	Polished
Inner Dimensions	260 (L) x 75 (W) x 75 (H) mm
Window	Tempered Glass
Window Glass Thickness	8 mm
Window Glass Diameter	75 mm
No. of Cable Entries	2
Cable Entry Size/Thread	M25/1.5
Max. Cable Passthrough Size	15 mm Max
Mounting	Wall mount with bracket or Base mount without bracket

ENVIRONMENT

Air Pressure	86 ~ 106KPa
Temperature	-40°C to +60°C with heater (-25°C without heater)
Humidity	≤95%RH (+25°C)


WEIGHTS (UNIT / SHIP)

Unit / Ship	7 / 9 Kg
-------------	----------

CAMERA OPTIONS

The housing can be supplied with Analog or Network Box Cameras and Lens or Motorized Zoom Camera Modules, upon request

EXTERNAL DIMENSIONS



ORDERING INFORMATION

PART NO	DESCRIPTION
AH35	Stainless Steel 316L Weatherproof IP68 Fixed Housing with Tempered Glass Window

OPTIONAL ACCESSORIES

AH	Thermostatically controlled heater (activates at 0°C) 110~230VAC (24VAC optional)
WD	Thermostatically controlled Windows Defroster (activates at 0°C) 110~230VAC (24VAC optional)
SS35	Stainless Steel 316L Sunshield
WB35	Stainless Steel 316L Wall mount bracket with swivel joint
AJ40	IP68 Junction/Termination Box